

## **BAG CARRYING BICYCLE RACK**

### **BACKGROUND OF THE INVENTION**

5

#### **Field of the Invention**

This invention relates to bicycle racks in general and more particularly to bicycle racks suitable for carrying a backpack or knapsack.

10

### **BACKGROUND OF THE INVENTION**

A variety of forms of racks, often caled "panniers" are available for attachment to horizontal carriers fixed over the rear wheel of a bicycle to extend downwardly, alongside the wheel. These panniers vary form one another in their convenience in loading and unloading their contents; the manner in which they are attached to the bicycle; their capacity; and other characteristics.

15

Such panniers include a platform rack mounted over the rear wheel by means of a system of strut members and forwardly projecting connectors which connect to the bicycle frame. The strut system is mounted adjacent to the axle of the rear wheel.

20

Most panniers are used for carrying parcels but the configuration of such panniers limits the variety of objects that can be carried in a safe and practical manner wherein

25

the object or objects won't fall off the pannier. That is why in practical use, people have resorted to putting their carryons in a bag or knapsack which can be more securedly attached to the pannier. The use of a bag is advantageous since the user is more familiar with the bag's size and configuration and therefore feels confident that objects placed inside will be secure and since they only have to figure how to attach the bag or knapsack to the pannier, since the bag or knapsack has a familiar size and shape, they can, feel confident that their bag or knapsack can be held securedly to the pannier. More and more so, people are using standard knapsacks which have the advantage of being transportable off the bicycle as well. Also, knapsacks have certain standard elements such as straps and a certain level of conformity in shapes and sizes which makes them particularly suitable for a pannier or bike rack.

Unfortunately, the prior art does not provide for mounting systems that are very reliable and they may not securedly hold a knapsack in situations where the travel is bumpy and as such, the knapsack may be dislodged from the rack or pannier.

A more secure and simple way to hold a knapsack needs to be found.

## **SUMMARY OF THE INVENTION**

In order to more appropriately hold a knapsack, a stretchable "fishnet" is used as a means to hold the knapsack. Because it is stretchable, it can conform to a variety of irregular shapes and hold them very securely.

It is therefore an object of this invention to provide for a bag carrying bicycle rack which can be attached over the back wheel of the bicycle.

5 It is another object of this invention to provide for a bag carrying bicycle rack having a lightweight but rigid armature.

It is yet another object of this invention to provide for a bag carrying bicycle rack having an adjustable hook to partially hold a knapsack in place.

10

It is a further object of this invention to provide for a bag carrying bicycle rack having a stretchable fishnet as means to securely hold a knapsack in place.

15

It is a final object of this invention to provide for a bag carrying bicycle rack having a back panel sheet between the bicycle wheel and the knapsack in order to protect the knapsack for dirt, mud and water projected from the wheel.

20

The foregoing and other objects, features, and advantages of this invention will become more readily apparent from the following detailed description of a preferred embodiment with reference to the accompanying drawings, wherein the preferred embodiment of the invention is shown and described, by way of examples. As will be realized, the invention is capable of other and different embodiments, and its several details are capable of modifications in various obvious respects, all without departing from the invention. Accordingly, the drawings and description are to be regarded as

25

illustrative in nature, and not as restrictive.

## **BRIEF DESCRIPTION OF THE PREFERRED EMBODIMENT**

**FIG. 1** A perspective elevation showing a bag carrying bicycle rack installed on a bicycle (seen in dotted lines)

**FIG. 2** Front elevation of the bag carrying bicycle rack with a knapsack inside and showing detail of the net and back panel sheet.

**FIG. 3** Front elevation of a second embodiment of the bag carrying bicycle rack with a knapsack inside and showing an alternate attachment using the struts.

**FIG. 4** A perspective rear elevation showing a bag carrying bicycle rack.

## **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT**

A bag carrying bicycle rack (10) is installed over the rear wheel (30) of a bicycle (12) and it is secured by a front attachment means (14) using any one of numerous means well known in the art. The bag carrying bicycle rack (10) uses either an existing bicycle rack (16) or is comprised of a similar component. The bicycle rack is further comprised of a pair of struts (18) situated on either side of the bicycle (12). The bag carrying bicycle rack (10) has a back panel sheet (20) to prevent any loose content from getting caught in the spokes of the bicycle wheel and a stretchable

fishnet (22).

The struts (18) have proximal ends (24) attached to the rack (16) and distal ends (26) fixedly attached to the hub (28) of the rear wheel (30) of the bicycle (12) using the bicycle's own nuts and bolts (32).

The back panel sheet (20) extends vertically downwards from the horizontal part (16) to which it is fixedly attached and is attached at its lower part to the hub (28) using the same nut and bolt (32). During assembly, both the distal end (26) and the back panel sheet (20) are attached together.

A stretchable fishnet (22) is releasably attached to the back panel sheet (20) by way of releasably detachable means comprised of a first releasable part (34) and a second releasable part (36).

An adjustable hook (38) completes the invention. The adjustable hook (38) has one of several adjustable means well known in the art.

By hanging a bag (40) from the hook (38) and then attaching the stretchable fishnet (22), a bag (40) can be secured into the bag carrying bicycle rack (10).

In **FIG. 3**, a second embodiment of the bag carrying bicycle rack (10) shows a higher location for the adjustable hook (38) as well as a strut attachment (42) which makes attaching the bag carrying bicycle rack (10) much easier. Using An "L" shaped rod

(44) as per **FIGS. 4ab** can allow the use of a variety of existing bicycle racks (16) wherein the “L” shaped rod (44) is fixedly attached upon. With the use of the strut attachment (42) on an existing bicycle rack (16) there is no need to dismantle nuts and bolts (32).

5

10

15

20

25